



# ***Filter-Online***

## ***Nordic Filtration Solution***

*... for better drinking water experience ...*

### ***Vana II Filter Housing***



**5"-10"-20" Slim / 10"-20" Jumbo**



... for better drinking water experience ...



#### Technical Data

Size	5" - 10" - 10(J) - 20" - 20(J)
Work Pressure	6bar
Work Temp.	5°-48° C
Media	Reinforced Polypropyl.
O-ring	NBR/Silicone
Connections	5"-10": 3/4 F 10"J: 1" F 20"J: 1½" F
Dimensions	5": 121x189mm (W/H) 10": 130x310mm (W/H) 20": 130x570mm (W/H) 10" J: 182x349mm (W/H) 20" J: 182x614mm (W/H)

## Vana II Filterhousing

Vana water filter housing with sump in transparent material.

Brass fitted inlet/outlet on all housings, reduces the risk of damage during installation and changing pressure.

Available in several sizes - accomodates different demands to flowrate.

- 5" Slim has an average flow rate of 15 l/min with filter cartridges.
- 9¾" Slim has an average flow rate of 28 l/min with filter cartridges.
- 20" Slim has an average flow rate of 56 l/min.
- 10" Jumbo has an average flow rate of 80 l/min.
- 20" Jumbo has an average flow rate of 160 l/min.

## Benefits

- Clear Sump - Visually inspectable filter cartridges.
- Brass fittings - Diminishes chance of connection burst in changing pressures.

